

Important Information About The WaterBoy Floral Watering Machine

MODEL # WB M-25



INSTRUCTIONS:

- CAREFULLY UNBOX THE WATERBOY**
Align the holes of the "T" Handle with the holes on the frame. Put the carriage bolts through and tighten up with the lock washers and wing nuts provided. Use pliers to tighten.
- ATTACH THE SINK TO HOSE ADAPTER**
Unscrew the aerator tip off your sink and screw on the Sink-to-Hose adapter which is found inside the Work Box on top of the WaterBoy.
- FILL THE WATERBOY**
Attach the Swivel Fitting that's on the end of the ON/OFF Flow Control Valve to the sink. Turn Valve to the open position & turn water on.
- WHEN WATERBOY IS FULL**
A) Shut off water, B) Turn off the valve, C) Unscrew from sink
- ATTACH THE WATER WAND**
Screw Water Wand to Swivel end of Valve. Keep Valve in OFF position.
- ADJUST THE FLOW**


Follow the 2 steps demonstrated on the bottom of this page. **NOTE: DON'T** just open flow valve to full on (too much flow!).




(A) INSERT "S" HOOKS INTO SIDE OPENINGS (B) AND POSITION BOX SO IT OPENS TOWARDS YOU.

CAUTION: DO NOT unscrew the Brass double female swivel off of the shut-off valve or it will leak and warranty will be void.

CAUTION: DO NOT Break or Remove seal. Releasing air from top chamber will disable the unit.




This is a 1/4 turn valve. **DO NOT** force past the off position or valve handle may snap off!



To adjust flow, with valve in the OFF position, use your fingers to **PRESS** on the Thumb Valve.



Slightly crack the flow valve. Flow starts off as a drip, continue until you adjustment is the way you like it.



Here's how it works! Normal water pressure the WaterBoy's unique tank! **IMPORTANT: DO NOT** break air cap seal on tank!

